



















Sika Srl

P. IVA: 02462820263

Tel. +39 0422 38 12 11 Riccardo Secco +39 334 67 62 754

Via della Pace 9, 31030 Dosson di Casier **Treviso - Italia**

r.secco@sika.tv www.sikaprofili.com













100% MADE IN TREVISO

BIG POST

This intermediate post is engineered in order to grant a high mechanical strength. The upper "H" shaped slots are suitable for the installation of the mobile wires and allow an easy lifting (mechanical using machines) of the wire. On the other side the "N" shaped lower slots are well designed and engineered for the Fix wire. On the lowest side of the posts is possible to find a last H shaped slots, suitable for the installation of the watering tube. Available on stock 2,8 meter long posts as our standard production (Different lengths are possible but only on demand).

Dimension	Raw material	Thickness	Weight	Slots	
	Corten	1,8 mm	2,05kg/m	H+N+H	
65 x 45 mm	Hot deep galvanized after forming	1,65 mm	1,89Kg/m	Slots suitable for the installation of the not tight wire and for	
	Hot deep galvanized	2 mm	2,29Kg/m	the watering tube	



Slots

SMALL POST

The small intermediate post has been engineered and then produced with multi-ribs in order to grant its performances. It is suitable for those companies whose are looking for a small but strength post. The slots available on these posts are only N Shaped. Available on stock 2,8 meter long posts as our standard production (Different lengths are possible but only on demand).

Slots

12 couples of

Dimension	Raw material	Thickness	Weight
	Corten	1,8 mm	1,84kg/m
51x41 mm	Hot deep galvanized after forming	1,65 mm	1,69Kg/m
	Hot deep galvanized after forming	2 mm	2,05Kg/m



LIGHT POST

This is a post engineered and produced with a multi ribs. Compared to the two previous one it is shorter and thinner post but as strong as the previous ones. It is equipped with N and H shaped alternate slots. Available on stock 2.0 meter long (Under customer's enquiry we suggest different sizes, between 1.8 and 2,3 meter).

Dimension	Raw material	Thickness	Weight
	Corten	1,5 mm	1,27kg/m
44x31 mm	Corten	1,8 mm	1,48Kg/m
	Hot deep galvanized after forming	1,65 mm	1,39Kg/m



STRONG POST

This is the end post. It is a big post, suitable to replace the concrete one used in the past. It is produced with slots and holes in order to let the installation of all the accessories for fixing and tensioning the wires. On the bottom side, there are 3 holes suitable for fixing the anti-breakthrough plate Available on stock 2,8 and 3.0 meter long.

Raw material Thickness

68x56 mm	Corten	2 mm	3,20Kg/m
	Hot deep galvanized after forming	2,15 mm	3,43Kg/m

ANTI-BREACJTHROUGH PLATE

It is an easy and fast solution for fixing the posts on the ground. After the installation of the Strong post on the ground, it is fixed using 3 latch-tightening screws. It is produced in stainless steel or pickled steel with hot deep coating operation after forming





TIE ROD

It is stainless steel made, fixed on the strong post it has the function of tensioning the wire.





"H" SHAPED SLOTS



"N" SHAPED SLOTS

Slots

10 couples of "N" and H

alternated shaped slots



COMBINED "H+N"





